(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 29 September 2005 (29.09.2005)

PCT

(10) International Publication Number WO 2005/090010 A1

(51) International Patent Classification?:

B25J 9/16

(21) International Application Number:

PCT/EP2005/051218

(22) International Filing Date: 16 March 2005 (16.03.2005)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/553.115 60/533,135 16 March 2004 (16.03.2004)

US 16 March 2004 (16.03,2004) US

(71) Applicant (for all designated States except US): ABB AB [SE/SE]; S-721 83 VÄSTERÅS (SE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): FORTELL, Håkan |SE/SE|; Julrosvägen 8, S-722 46 VÄSTERÅS (SE). JER-REGARD, Henrik [SE/SE]; Bernsborgsstigen 18, S-722 18 VÄSTERÄS (SE).

(74) Agent: ABB AB; Legal & Compliance, Intellectual Property, S-721-78-VÄSTERÄS (SE).


- (81) Designated States (unless otherwise indicated, for every kind of national protection available); AE, AG, AL, AM. AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FL GB, GD, GE, GH, GM, HR, HU, ID, H., IN, IS, JP, KE, KG. KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ. TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA. SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

[Continued on next page]

(54) TIGE: SYSTEM OF MANUPULATORS AND METHOD FOR CONTROLLING SUCH A SYSTEM



(57) Abstract: A system of manipulators comprises several manipulators (1, 2, 3), namely robots (1, 2) and/or external axes (3) such as workstations or transport tracks, whereby each manipulator is controlled by a control system (21) via communication means and is programmed to carry out a plurality of tasks. The system of manipulators is movable in a first coordinate system (4) and a second coordinate system (5, 6, 55) is defined for each manipulator, so that one part of said manipulator, e.g. its tool center point, stands still in said second coordinate system, which is movable relative to the first coordinate system.

WO 2005/090010 A1

before the expiration of the time limit for amending the For two-letter codes and other abbreviations, refer to the "Guidclaims and to be republished in the event of receipt of amendments

ance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.